



30W LED Flood Light


Material	Aluminum Alloy, Glass
Voltage	AC 100~240V
Protection Rank	IP65
CCT	2700-3200K
	4000-4500K
	6000-7000K
CRI	>70
Beam Angle	120°
Power consumption	30W
Power Factor	>0.9
Luminous efficacy	70 lm/W ±10%
Flux	1800 lm ±10%
Size	213 x 171 x 67mm





50W LED Flood Light

Material	Aluminum Alloy, Glass
Voltage	AC 220V
Module input current	247mA
Operating temperature	- 20 °C ~ + 45 °C
Storage temperature	- 30 °C ~ + 60 °C
Net Weight	780g
Protection Rank	IP65
CCT	5900K
CRI	>70
Beam Angle	120°
Power consumption	50W±10%
Power Factor	>0.9
Luminous efficacy	75 lm/W
Flux	3500 lm
Size	190 x 251 x 52mm



TYC Brother Industrial Co., Ltd


HEAD OFFICE : 72-2 Shin-leh Rd., Tainan 702, Taiwan
TEL: +886-6-2658780 FAX: +886-6-2639608
<http://www.tyc.com.tw>





50W LED Flood Light

Material	Aluminum Alloy, Glass
Voltage	AC 100~240V
Module input current	550mA
Operating temperature	- 20 °C ~ + 45 °C
Storage temperature	- 30 °C ~ + 60 °C
Net Weight	1370g
Protection Rank	IP65
CCT	6150K
CRI	>70
Beam Angle	120°
Power consumption	50W±10%
Power Factor	>0.9
Luminous efficacy	75 lm/W
Flux	4000 lm
Size	240 x 220 x 77mm





50W LED Flood Light


Material	Aluminum Alloy, Glass
Voltage	AC 100~240V
Protection Rank	IP65
CCT	2700-3200K
	4000-4500K
	6000-7000K
CRI	>70
Beam Angle	120°
Power consumption	50W
Power Factor	>0.9
Luminous efficacy	80 lm/W ±10%
Flux	3000 lm ±10%
Size	241 x 193 x 72mm





50W LED High-Bay Light


Material	Aluminum Alloy, PC
Voltage	AC 100~240V
Operating temperature	- 20 °C ~ + 50 °C
Storage temperature	- 20 °C ~ + 60 °C
Net Weight	1900g
CCT	5700K
CRI	>80
Beam Angle	60°
Power consumption	50W
Power Factor	>0.95
Luminous efficacy	>95 lm/W
Flux	4889 lm
Size	Ø350 x 400mm





60W LED High-Bay Light

Material	Aluminum Alloy, PC
Voltage	AC 90~265V
Operating temperature	- 20 °C ~ + 50 °C
Storage temperature	- 20 °C ~ + 60 °C
Net Weight	2200g
CCT	3000K / 5500K
CRI	>75
Beam Angle	60°
Power consumption	60W
Power Factor	>0.95
Luminous efficacy	95 lm/W
Flux	6142 lm
Size	Ø437 x 320mm





LINEAR LED High-Bay

Material	Aluminum Alloy, IRON
Voltage	AC 120~277V
Operating temperature	- 30 °C ~ + 40 °C
Net Weight	7246g(80W) / 7700g
CCT	5000K
CRI	84
Beam Angle	110°
Power consumption	80W / 160W / 240W
Power Factor	>0.95
Luminous efficacy	84 lm/W
Size(80W)	304 x 101 x 1220mm
Size(160W)	406 x 101 x 1220mm
Size(240W)	406 x 101 x 1220mm

